



Medium wire stapler

Technical specifications

Dimension (LxWxH)	305x50x229 mm
Net weight	1,21 kg
Firing mode	Dual
Air inlet	1/4" female NPT
Operating pressure	4,8 - 8,3 bar
Air consumption (at 60 shots per minute)	54,4 l/m
Operating temperature range	-18 - 49 °C
Sound pressure level (Lpa)	83 dB
Sound power level (Lwa)	89 dB
Vibration level	2,5 m/s ²
Fastener driving power	19 J
Shots / second	10
Magazine capacity	168 pieces
Gauge	18 ga.
Collation type 1	Glue collated
Collation angle	0 °


Applications

For varied component assemblies in furniture manufacturing, such as drawers, casebacks, cabinet frame assembly and upholstery spring attachment. Used in underlayment sheathing, paneling, molding/trim, soffits, pre-finished gypsum and siding for on-site and manufactured housing. Used in a variety of general woodworking and wood assembly operations, including lattice and bed-spring attachment.

Features & Benefits

- Lightweight for ease of handling
- Ergonomically designed with a comfort-grip handle to reduce fatigue
- Adjustable depth-of-drive for precise staple setting
- 40% more power than comparable tools
- Heavy duty components, including an aluminum sleeve and piston, mean rugged durability even in high volume production environments
- No-mar pad keeps work surfaces free of marks
- Oil-free design means easier maintenance and no lubrication to stain fine wood
- Muffler ensures quiet operation

Fastener specification



Description

SLS25XP-M, mw stapler

Art. Nr.

822010N

EAN code

0741474040764